

Modèles	Visuels	Descriptifs	Finitions	PPI € TTC/paire
fact <sup>®</sup> 8 signature		<p><b>Freq response</b> : 28Hz – 30kHz  <b>Sensitivity</b> : 89dB 1W 1m  <b>Effective ATL</b> : 3m (9.8ft)  <b>Impedance</b> : 8 Ohms  <b>Drive Units</b> : LF 2 x fact 140mm (5 ½") precision drivers                      HF fact 19mm high res, SONOMEXTM soft dome, ferrofluid cooled  <b>Crossover Freq</b> : 1.7kHz  <b>Input connectors</b> : 2 pairs 4mm PMC Ag terminals (Bi-wire or Bi-amp)  <b>Dimensions</b> :                      H 1030mm (40.6") + 25mm spikes                      W 155mm (6.1") + 80mm ingot feet                      D 380mm (15") + 10mm Grille                      + 23mm Ag terminal  <b>Weight</b> : 20.0kg (44lbs) ea.</p>	 White Silk  Metallic Graphite  Walnut	13 490 €
fact <sup>®</sup> 12 signature		<p><b>Freq response</b> : 26Hz – 30kHz  <b>Sensitivity</b> : 84dB 1W 1m  <b>Effective ATL</b> : 3.3m (11ft)  <b>Impedance</b> : 8 Ohms  <b>Drive Units</b> : LF 2 x fact 140mm (5 ½") super-long-throw                      MF 1 x fact 50mm (2.0") super clarity soft dome, ferro-fluid cooled, mid-range                      HF 1 x fact 19mm high-res, SONOMEXTM soft dome, ferro-fluid cooled  <b>Crossover Freq</b> : 400Hz, 4kHz  <b>Input connectors</b> : 3 pairs 4mm PMC Ag terminals (Tri-wire or Tri-amp)  <b>Dimensions</b> :                      H 1110mm (43.7") + 25mm spikes                      W 168mm (6.1") + 100mm ingot feet                      D 420mm (16.5") + 10mm Grille                      + 23mm Ag terminal  <b>Weight</b> : 26.0kg (57lbs) ea.</p>	 White Silk  Metallic Graphite  Walnut	22 680 €
factfenestria		<p><b>Type</b>: 3-way passive, twin cabinet, plus MF/HF nest module  <b>Crossover frequency</b>: 380Hz &amp; 3.8kHz  <b>Dimensions including plinth</b>: H 1700mm (66.9") x W 370mm (14.6") x D 623mm (24.5") including binding posts  <b>Drive units</b>: LF - 6.5" transverse-weave, carbon-fibre, multicellular-core piston driver                      MF - 75mm rear-chambered, soft-dome driver isolated in nest mount                      HF - 19.5mm, SONOMEXTM soft-dome, ferro-fluid-cooled driver with 36mm wide surround, neodymium magnet, micro custom chassis, silicone Aureole™ isolation mount                      Effective ATL™ length: 2 x 2.4m (7.9ft)  <b>Frequency response</b>: 23Hz - 25kHz  <b>Impedance</b>: 4 Ohms  <b>Input connectors</b>: Hex-Rhodium 4mm binding posts (3 pairs) accepting 4mm plugs, spades &amp; bare wire  <b>Sensitivity</b>: 86dB @ 1W, 1m  <b>Weight</b>: 80kg (176 lbs) each, including plinth  <b>Recommended amplifier power</b>: 200W - 1kW</p>	 White Silk  Rich Walnut  Graphite  Tiger Ebony	67 720 €