

Modèles	Visuels	Spécifications	Finitions	PPI € TTC
<p>prodigy1 Enceinte 2 voies</p>    	<p>Freq response 50Hz – 25kHz Sensitivity 87.5dB SPL 1W 1m Rec. amp power 20 - 250W Effective ATL™ 1.91m 6.3ft Impedance 6 Ohm Drive units LF PMC 5.25"/133mm natural fibre long-throw LTTM HF PMC 27mm /1" soft dome Peak SPL 123dB SPL Crossover freq. 1.7kHz Horizontal Directivity 80 degrees Vertical Directivity 80 degrees Input connectors One pair 4mm binding posts Dimensions H 320mm 35.7" (+20mm spikes) W 162mm 6.4" D 237mm 9.3" (+10mm optional grille) Weight 4.5kg 9.9lbs ea. Finish Silk Black Options prodigy1 grille</p>	 <p>BLACK</p>	<p>Paire 1 690 €</p>	
<p>prodigy5 Enceinte colonne 2 voies</p>   	<p>Freq response 35Hz - 25kHz Sensitivity 87.3dB SPL 1W 1m Rec. amp 20 - 250W Effective ATL™ 1.96m 6.4ft Impedance 6 Ohm Drive units LF PMC 5.25"/133mm natural fibre long-throw LTTM HF PMC 27mm /1" soft dome Peak SPL 124dB SPL Crossover freq. 1.7kHz Horizontal Directivity 80 degrees Vertical Directivity 70 degrees Input connectors One pair 4mm binding posts Dimensions H 905mm 40" (+20mm spikes) W 165mm 6.5" (233mm incl. plinth bars) D 237mm 9.3" (+10mm optional grille) Weight 10kg 22lbs ea. Finish Silk Black Options prodigy5 grille</p>	 <p>BLACK</p>	<p>Paire 2 690 €</p>	
<p>prodigy1 cache</p> 				<p>120 €</p>
<p>prodigy5 cache</p> 				<p>120 €</p>